

SCALEOVIEW L19W-10

19 Inch LCD widescreen Display

Issue May 2008

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L19W-10 widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L19W-10 fits perfectly into your home environment.

Highlights

- § 19-inch widescreen display for a perfect viewing experience
- § Best performance to an affordable price
- § Stylish black design with a silver front
- § Very easy and comfortable to use
 - Plug & Play
 - Auto-adjust
 - Easy-to-use OSD menu

Ergonomics

- § Optimum flicker-free and distortion-free picture
- § Excellent colour purity
- § Well balanced brightness uniformity
- § High contrast up to 800:1
- § Space saving design

Technical highlights

- § 19" (48.1cm) LCD widescreen display
- § Excellent contrast up to 800:1
- § Brightness 300 cd/m²
- § Fast response time (typ.) 5 ms
- § Internal power supply

Reliability

- § Low power consumption (EPA 'On Mode': 19 W)
- § Power management according to EPA
- § Guaranteed quality and stability



Visible screen diagonal	19 inch (48.1 cm)	
Resolutions		
Pixels	1440 x 900	
Pixels*	1280 x 768	
* expanded		
Picture size	410 x 256 mm	
Colours	16.7 million	
Pixel Pitch	0.285 mm	
Frequencies		
Horizontal	30 - 82 kHz	
Vertical	55 - 75 Hz	
Brightness (typical)	300 cd/m ²	
Contrast up to	800:1	
Viewing angle (typical)	CR>10:1	CR>5:1
Horizontal	170°	160°
Vertical	170°	160°
Response time (typical)	5 ms	
Plug and Play	VESA DDC2B	
Setting options		
Brightness (Back light control)		
Contrast, Volume control		
Picture position (horizontal and vertical), H-size, Phase,		
Color temperature and individual color setting		
Auto-adjust (direct access key)		
Activate factory settings		
Menu language		
OSD Language		
English, German, Spanish, French, Italian, Russian,		
Swedish, Dutch		
Base		
Tilt angle	-5°/ +20°	
Audio characteristics		
Audio signal input	3.5mm stereo phone jack	
Audio output	1 W (L) + 1 W (R)	

Electrical values (internal power supply)		
Rated voltage	100 - 240 V	
Frequency	50 - 60 Hz	
Power draw		
EPA 'On Mode'	19 W	
Max.	<50 W	
EPA 'Off Mode'	0.7 W	
Protection class	1	
Temperatures/ dimensions/ weight		
Ambient temperature (to IEC721):		
Working (recommended)	5°C to 35°C	
Storage	-20°C to 60°C	
Dimensions (H x W x D):	354.5 x 443 x 200,3 mm	
Weight (Monitor only)	4.15 kg	
Reliability		
MTBF (demonstrated)	70,000 h	
Lifetime of LCD backlight	50,000 h	
(brightness > 50 % of original brightness)		
Compliance with standards		
Product safety	EN60950	
Ergonomics	GS mark	
	ISO13406-2	
	(Pixel fault class II)	
Radiation immunity and	CE certification according	
RFI suppression	to EC Directive	
	2004/108/EEC	
	(EN55022/B, EN55024	
	EN61000-3-2/-3);	
	TCO'03	
Ecology	RoHS,	
	IT-Eco-declaration, Energy	
Video input	1 x D-SUB	
Accessories		
Power cable (1.5 m)*	For wall socket	
	(Euro-Schuko-Type CEE7)	
Data cable (1.5 m)*	D-SUB (15-pin)	
Audio cable (1.8 m)*	3.5mm stereo phone jack	
* detachable on display		
Special features	Standardized mounting	
	interface according	
	VESA FPMPI (100 mm)	
	Kensington Lock	
Order code	S26361-K1248-V170	
EAN	4333643448851	